



CoG: 4400 mm  
 Thickness: 3,3 mm  
 Weight: 54,5 kg

|        |            |  |  |   |               |                 |                     |               |
|--------|------------|--|--|---|---------------|-----------------|---------------------|---------------|
| Part 3 |            |  |  |   |               |                 |                     |               |
| Part 2 |            |  |  |   |               |                 |                     |               |
| Part 1 | 1308020011 | Con. lighting column 8,00 m                      |  |   |               |                 |                     |               |
|        |            | MATERIAL<br>EN AW-6060 T66                       |  | REMARKS<br>Tolerance on Radius between 0 and +10%   |               |                 |                     |               |
|        |            | Hydro Extrusion Drunen B.V.                      |  | THIS DRAWING REMAINS PROPERTY OF HYDRO EXTRUSION DRUNEN B.V. AND MAY WITHOUT THE WRITTEN PERMISSION OF THE OWNER NOT BE MULTIPLIED, BE USED FOR THIRD PARTIES OR BE GIVEN TO THIRD PARTIES FOR PERUSAL. |               | SCALE<br>1 : 52 | ORG.DAT<br>27-10-09 |               |
|        |            | Con. lighting column 8,00 m                      |  |   |               | DRAWN BY<br>PE  | REV.DAT             |               |
|        |            |  |  |   |               | SIGN            | MUT.DAT<br>05-07-11 |               |
|        |            | TOLERANCES BY EN40<br>UNLESS SPECIFIED OTHERWISE | DIMENSIONS IN MM<br>UNLESS SPECIFIED OTHERWISE | AMERICAN PROJECTION   | DRAWINGNUMBER |                 |                     | LAST REVISION |
|        |            |  |  |   | 1308020011    |                 |                     |               |
| 2      | 1          |  |  |   |               |                 |                     |               |