


BUTT AND PARALLEL CONNECTORS

for Copper conductors



butt connectors




parallel connectors

Recommended crimping tools are shown on pages 120 to 147, 184, 243.

PVC insulated


Conductor Size sqmm (AWG)	Type	ø mm	L mm	Quantity Box/Bag
0,25÷0,5 (24÷20)	PL01-M*	3,0	25,0	3.000/100
0,25÷1,5 (22÷16)	PL03-M	4,0	25,0	1.000/100
1,5÷2,5 (16÷14)	PL06-M	5,0	25,0	1.500/100
4÷6 (12÷10)	PL1-M	6,5	32,0	500/100
0,25÷1,5 (22÷16)	PL03-P*	4,0	20,0	3.000/100
1,5÷2,5 (16÷14)	PL06-P*	5,0	16,0	2.000/100



BUTT CONNECTORS


for Copper conductors

Recommended crimping tools are shown on pages 120 to 147, 184, 243.




Polyamide PA6.6 insulated

Conductor Size sqmm (AWG)	Type	ø mm	L mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	NL03-M	4,0	25,0	1.000/100
1,5÷2,5 (16÷14)	NL06-M	5,4	25,5	1.500/100
4÷6 (12÷10)	NL1-M	7,6	32,0	500/100
10 (8÷7)	NL2-M	8,0	43,0	500/100
16 (6÷5)	NL3-M	9,2	44,0	400/100



Recommended crimping tools are shown on page 122.



PE HD insulated, heat shrinkable

Conductor Size sqmm (AWG)	Type	ø mm	L1 mm	L2 mm	Quantity Box/Bag
0,5÷1,5 (22÷16)	WL03-M	1,7	15,0	36,0	1.500/100
1,5÷2,5 (16÷14)	WL06-M	2,3	15,0	36,0	1.000/100
4÷6 (12÷10)	WL1-M	3,5	15,0	41,0	500/100


- Max operating voltage: 600 V
- Shrink temperature: 150 °C
- Protection: IP68



CLOSE END CONNECTORS

for Copper conductors

Recommended crimping tools are shown on pages 120 to 147, 184, 243.



Polyamide PA6.6 insulated

Conductor Size sqmm (AWG)	Type	ø mm	L mm	Quantity Box/Bag
0,25÷1,5 (22÷16)	NL03-P	7,9	21,0	1.000/100
1,5÷2,5 (16÷14)	NL06-P	7,9	19,9	1.000/100
	NL06-PB	6,5	13,6	1.500/100
4÷6 (12÷10)	NL1-P	10,5	21,5	500/100
	NL1-PG	9,0	17,8	1.000/100



*Not UL approved