



CoG: 5300 mm
 Thickness: 3,3 mm
 Weight: 64,7 kg

| | | | | | | | | |
|--------|------------|------------------------------|--|---|---------------------|---------------|--------|---------------------|
| Part 3 | | | | | | | | |
| Part 2 | | | | | | | | |
| Part 1 | 1310020025 | Con. lighting column 10,00 m | | | | | | |
| | | MATERIAL EN AW-6060 T66 | | REMARKS Tolerance on Radius between 0 and +10% | | | | |
| | | Hydro Extrusion Drunen B.V. | | THIS DRAWING REMAINS PROPERTY OF HYDRO EXTRUSION DRUNEN B.V. AND MAY WITHOUT THE WRITTEN PERMISSION OF THE OWNER NOT BE MULTIPLIED, BE USED FOR THIRD PARTIES OR BE GIVEN TO THIRD PARTIES FOR PERUSAL. | | SCALE | 1 : 63 | ORG.DAT 27-10-09 |
| | | Con. lighting column 10,00 m | | | | DRAWN BY | PE | REV.DAT 09-06-10 |
| | | | | | | SIGN | mre | MUT.DAT 27-10-09 |
| | 09-06-10 | DATE | TOLERANCES BY EN40 UNLESS SPECIFIED OTHERWISE | DIMENSIONS IN MM UNLESS SPECIFIED OTHERWISE | AMERICAN PROJECTION | DRAWINGNUMBER | | LAST REVISION |
| -2 | -1 | 1 | | | | 1310020025 | | 1 |