



**PILLAR SPECIFICATION:**

Type:	SMP30 Mini Pillar
Weight:	16Kg
Working depth:	130mm
Door aperture:	W142mm x H580mm
Backboard:	12mm thick fully treated ply
Backboard size:	W150mm x H600mm
Construction:	3mm steel
Corrosion protection:	Hot dipped galvanised BS EN ISO 1461
Door:	Single door lift off
Door lock:	Tri head
Root:	Fixed (not detachable)
Door label:	Hazard warning to BS 5378

**OPTIONS:**

- Ventilation louvre slots (door only)
- Standard powder coat finish Green RAL6005
- Standard powder coat finish Grey RAL7000
- Standard powder coat finish black RAL9005
- Other non-standard finishes available on request

**Notes:-**

This drawing is supplied for illustration purposes only.

Charles Endirect standard BDP & CFP range of feeder pillars have a detachable root section. the smaller pillars SMP, FMP have a fixed root.

The root section is usually planted below ground and bolted to a secure concrete foundation.

The foundation size & concrete mix will need to be specified by your civil engineer with respect to the pillar size, weight, site location & ground soil conditions.

Issue	Status	Date	Approval
A	Proposed	08/03/18	ISW

Drawn:-	ISW
Dim:-	mm
Scale:-	NTS

**Charles Endirect**  
*Ingenuity at work*

Wessex Way, Wincanton Business Park  
 Wincanton, Somerset, BA9 9RR

T: +44 01963 828400  
 F: +44 01963 828401  
 e: info@charlesendirect.com  
 www.charlesendirect.com

ALL SUBJECT MATTER OF THIS DRAWING IS THE SOLE PROPERTY OF CHARLES ENDIRECT LTD. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CHARLES ENDIRECT LTD IS PROHIBITED.

Project:-  
**CEL STANDARD PILLAR SMP30**

Title:-  
**SMP30**

Drg No:-  
**SMP30**

Sheet **1** of **A3**

